

DECLARATION OF PERFORMANCE DoP. 406/13

| 1. | Product | Load-bearing profiled sheet | | | |
|----|---|--|---|-------------------------------------|--|
| 2. | Product type identific | W-70/900, W-115/750, W-130/950 ja W-155/840. | | | |
| 3. | Intended Use | Self-supporting metal sheet products for roofs, internal and external wall cladding. | | | |
| 4. | Manufacturer | Weckman Steel Oy, Härkäläntie 72, 19110 Vierumäki | | | |
| 5. | - | - | | | |
| 6. | Building Product of co | onstancy of performance assessment and verification(s): AVCP- class 3 | | | |
| 7. | Constancy of VTT Expert Services - in accordance with the three product types, the initial testing and configuration, | | | | |
| | performance | system-class and te | t reports issued (0809) has been completed. | | |
| | evaluation and | , | | | |
| | examination system | | | | |
| 9. | Declared performance | | | | |
| | Basic features | | Performance level | Harmonised Technical Specifications | |
| | Release of dangerous substances: | | NPD | | |
| | Shelf life: | | NPD | 1 | |
| | The vapor and air permeability: | | NPD | SFS-EN 14782: 2006 | |
| | Shelf life: | | NPD | | |
| | Water permeability: | | NPD | | |
| | Exposure to fire needs below: | | Broof t1, t2, t3 | | |
| | Fire behavior: | | A1, "CWFT" | | |

10. Signed on behalf of the manufacturer:

Vierumäki 29.1.2014

Jan South

Janne Ylärakkola

Quality Manager