

DECLARATION OF PERFORMANCE DoP. 606/16

| 1. | Product | Interlocking roof sheet | | | |
|----|----------------------------------|--|---|-------------------------------------|--|
| 2. | Product type identific | 2 Progant -475 | | | |
| 3. | Intended Use | For fully supported structures as roofing material. | | | |
| 4. | Manufacturer | Weckman Steel Oy, Härkäläntie 72, 19110 Vierumäki | | | |
| 5. | - | | | | |
| 6. | Building Product of co | onstancy of perform | nance assessment and verification(s): | AVCP- class 3 | |
| 7. | Constancy of | VTT Expert Services - in accordance with the three product types, the initial testing and configuration, | | | |
| | performance | system-class and t | t reports issued (0809) has been completed. | | |
| | evaluation and | | | | |
| | examination system | | | | |
| 9. | Declared performance | | | | |
| | Basic features | | Performance level | Harmonised Technical Specifications | |
| | Release of dangerous substances: | | NPD | SFS-EN 14783: 2006 | |
| | Shelf life: | | NPD | | |
| | The vapor and air permeability: | | NPD | | |
| | Shelf life: | | NPD | | |
| | Water permeability: | | NPD | | |
| | Exposure to fire needs below: | | Broof t1, t2, t3 | | |
| | Fire behavior: | | A1, "CWFT" | | |

Signed on behalf of the manufacturer:

Vierumäki 21.9.2016

Jan South

Janne Ylärakkola

Quality Manager



Weckman Steel Oy

Vierumäki Iisalmi 03-88870

Härkäläntie 72 Muovikatu 12 www.weckmansteel.fi 19110 Vierumäki 74120 Iisalmi